

Explanation of Amendments in the Claims:

1.(cancelled)

2.(previously cancelled)

3.(previously cancelled)

4.(cancelled).

5.(cancelled).

6.(cancelled).

7.(cancelled).

8.(cancelled).

9.(cancelled).

10.(previously cancelled)

11.(previously cancelled)

12.(previously amended)     A method of detecting moisture in an absorbent material, the method comprising:

providing a tape formed by a substrate of a dielectric, hydrophobic material, a layer of a mounting adhesive on a bottom surface of the substrate and a first and a second spaced apart elongate parallel conductors mounted on a top surface of the substrate and extending therealong;

attaching the tape by the adhesive on to a surface of the material so as to mount the two conductors on or adjacent the surface of the material;

providing at each of a plurality of longitudinally spaced locations along the adhesively attached tape a respective pair of plurality of pairs of conductive probes;

wherein each probe is a rigid elongate conductive element of a corrosion resistant material;

wherein the probes of each pair are electrically separated each from the other;

forcing each probe longitudinally into the material at the respective location so as to penetrate through the surface of the material and to engage into the absorbent material;

as each probe of each pair is forced into the absorbent material, causing the probe of each pair to penetrate a respective one of penetrating the first and second conductors of the tape with a respective one of a pair of conductive probes such that each of the conductive probes engages into the absorbent material and is electrically connected to the respective one of the first and second conductors by penetrating therethrough;

applying a voltage across the two conductors; and

monitoring currents passing between the conductors so as to detect changes in resistance between the conductors caused by moisture in the material.

13.(previously amended) A method according to claim 12 wherein the conductors of the tape are covered by a protective layer of non-hygroscopic, water pervious, dielectric material secured to the to the top surface of the substrate and extending over the conductors.

14.(previously cancelled)

15.(previously amended) A method according to claim 12 wherein each of the conductors is a flat metal strip at least 6.5 mm wide.

16.(previously amended) A method according to claim 12 wherein the conductors are spaced apart by a distance of at least 13 mm.

17.(previously cancelled)

18.(cancelled)

19.(previously amended) A method according to claim 12 wherein the absorbent material is a moisture permeable element of a building construction.

20.(cancelled)

21.(currently amended) A method of detecting moisture in an absorbent

material, the method comprising:

providing a tape formed by a substrate of dielectric, hydrophobic material, a layer of a mounting adhesive on a bottom surface of the substrate and a first and a second spaced apart, elongate, parallel conductors mounted on a top surface of the substrate and extending therealong;

attaching the tape by the adhesive on to a surface of the material so as to mount the two conductors on or adjacent the surface of the material;

providing at each of a plurality of longitudinally spaced locations along the adhesively attached tape a respective pair of plurality of pairs of conductive probes;

wherein each probe is a rigid elongate conductive element of a corrosion resistant material;

forcing each probe longitudinally into the material at the respective location so as to penetrate through the surface of the material and to engage into the absorbent material;

~~penetrating into the absorbent material through a surface of the material a plurality of pairs of conductive probes;~~

the probes of each pair being electrically separated each from the other and spaced apart such that current can flow through the material between the probes when moisture is present in the material;

~~the probes being located at spaced positions along a length of the material to be monitored;~~

as the first probe of each pair is forced into the absorbent material, causing the first probe to engage the first conductor of the tape such that the first conductive probe is electrically connected to the first conductor;

as the second probe of each pair is forced into the absorbent material, causing the second probe to engage the second conductor of the tape such that the second

conductive probe is electrically connected to the second conductor;

~~electrically connecting one probe of each pair to the first one of the conductors;~~

~~electrically connecting a second probe of each pair to the second one of the conductors;~~

applying a voltage across the first and second conductors; and

monitoring currents passing between the conductors so as to detect changes in resistance between the conductors caused by moisture in the material.

22.(currently amended) A method according to Claim 21 ~~20~~ wherein the first and second conductors of the tape are covered by a protective layer of non-hygroscopic, water pervious, dielectric material secured to the top surface of the substrate and extending over the conductors.

23.(currently amended) A method according to Claim 21 ~~20~~ wherein each of the first and second conductors is a flat metal strip at least 6.5 mm wide.

24.(currently amended) A method according to Claim 21 ~~20~~ wherein the first and second conductors are spaced apart by a distance of at least 13 mm.

25.(currently amended) A method according to Claim 21 ~~20~~ wherein each probe is a rigid elongate conductive element of corrosion resistant material which is forced into the material longitudinally of the element.

26.(currently amended) A method according to Claim 21 ~~20~~ wherein the absorbent material is a moisture permeable element of a building construction.

Please add new claims as follows:

27.(new) A method of detecting moisture in an absorbent material, the method comprising:

providing a tape formed by a substrate of dielectric, hydrophobic material, a layer of a mounting adhesive on a bottom surface of the substrate and a first and a second

spaced apart, elongate, parallel conductors mounted on a top surface of the substrate and extending therealong;

wherein each of the first and second conductors is a flat metal strip laid flat on the top surface of the substrate;

wherein the first and second conductors of the tape are covered along the tape by a protective layer of non-hygroscopic, water pervious, dielectric material secured to the top surface of the substrate and extending over the conductors;

attaching the tape by the adhesive on to a surface of the material so as to mount the two conductors on or adjacent the surface of the material;

applying a voltage across the first and second conductors; and

monitoring currents passing between the conductors so as to detect changes in resistance between the conductors caused by moisture in the material.

28.(new) A method according to Claim 27 wherein the absorbent material is a moisture permeable element of a building construction.